

Amendments to the claims:

Please replace all prior versions and listings of the claims with the following amended claims:

Listing of Claims:

1. (Currently Amended) A device comprising a cleaning head, the cleaning head comprising:
 - a) a first region with a first support surface having bristles protruding therefrom, the first support surface being configured to move in a first direction; and
 - b) a second region with a second support surface having a first squeegee element and bristles protruding therefrom, the squeegee element having elongated walls that protrude to form a curved elongated wiping edge configured to treat a working surface,wherein the second support surface is configured to move separately from the first support surface in a second direction that is different from the first direction and wherein a portion of the bristles protruding from the first support surface and the second support surface flank opposed sides of the elongated wiping edge formed by the elongated walls.
2. (Previously Presented) The device of claim 1, wherein the first support surface has a second squeegee element protruding therefrom.
3. (Canceled).
4. (Previously Presented) The device of claim 1, wherein at least one of the first support surface and second support surface is configured to rotate or oscillate.
5. (Canceled).
6. (Previously Presented) The device of claim 1, wherein the elongated walls of the first squeegee element encircles an inner squeegee region and encircles at least a portion of the bristles.

1 7. (Canceled).

1 8. (Canceled).

1 9. (Canceled).

1 10. (Canceled).

1 11. (Canceled).

1 12. (Currently Amended) A device comprising a motorized cleaning head, the motorized
2 cleaning head comprising:
3 a) a first region with bristles protruding from a first support surface that is
4 configured to automatically move in a first direction; and
5 b) a second region comprising:
6 i. a squeegee member with curved elongated squeegee walls that
7 protrude from a second support surface to form a curved elongated
8 wiping edge; and
9 ii. bristles that protrude from the second support surface,
10 wherein the second support surface is configured to automatically move in a second
11 direction that is different from the first direction, wherein a portion of the bristles
12 protruding from the first support surface and the second support surface flank opposed
13 sides of the curved elongated edge formed by the curved elongated walls.

1 13. (Canceled).

1 14. (Previously Presented) The device of claim 12, wherein at least one of the first support
2 surface and the second support surface is configured to rotate or oscillate.

1 15. (Canceled).

1 16. (Previously Presented) The device of claim 12, wherein the curved elongated squeegee
2 walls encircle at least a portion of the bristles that protrude from the second support

3 surface.

1 17. (Canceled).

1 18. (Canceled).

1 19. (Previously Presented) The device of claim 12, wherein the first support surface and the
2 second support surface are both configured to rotate or oscillate.

1 20. (Currently Amended) A cleaning device comprising a detachable cleaning head
2 comprising:

- 3 a) a first section with a first support surface with a first squeegee wiping
4 element protruding therefrom and being configured to automatically rotate
5 or oscillate while coupled to a motorized handle; and
- 6 b) a second section with a second support surface with a second squeegee
7 wiping element protruding therefrom and surrounding the first section and
8 being configured to automatically rotate or oscillate while coupled to the
9 motorized handle, wherein the second section is configured to
10 automatically rotate or oscillate at a rate or direction that is different from
11 that of the first section wherein the squeegee protruding from the first
12 support surface and the squeegee protruding from the second support
13 surface each has opposed walls that form elongated wiping edges; and
14 bristles protruding from ~~at least one of the first support surface and the~~
15 ~~second support surface wherein the bristles protrude~~ from positions
16 between the first squeegee wiping element and the second squeegee
17 wiping element.

1 21. (Canceled).

1 22. (Canceled).

1 23. (Canceled).

1 24. (Canceled).

1 25. (Currently Amended) A device comprising a cleaning head comprising:

- 2 a) a first support surface ~~with a first wiping region~~; and
- 3 b) a second support surface that is separate from the first support surface with a
- 4 ~~second wiping region~~, wherein ~~both of the first wiping region surrounds the~~
- 5 ~~second wiping region~~, and the first support surface and the second support surface
- 6 ~~are configured to move automatically~~, wherein ~~at least one of the first wiping~~
- 7 ~~region support surface~~ and the second ~~wiping region support surface~~ comprises a
- 8 squeegee element with elongated walls that protrude to form a top wiping edge,
- 9 and ~~at least one of both of the first wiping region support surface~~ and the second
- 10 ~~wiping region support surface~~ comprises bristles and wherein at least one of the
- 11 first support surface and the second support surface is configured to move
- 12 automatically and independently of the other of the first support surface and the
- 13 second support surface, while the cleaning head is coupled to a motorized handle.

1 26. (Currently Amended) A cleaning head device comprising:

2 a) a cleaning head comprising:

- 3 [[a)] i) a first support surface with a first squeegee element with a first curved
- 4 elongated wiping edge and a first set of curved elongated walls and bristles
- 5 protruding therefrom; and
- 6 [[b)] ii) a second support surface that is separate from the first support surface, the
- 7 second support surface having a first second squeegee element with a
- 8 second curved elongated wiping edge and a second set curved elongated
- 9 walls and bristles protruding therefrom, wherein a portion of the bristles
- 10 protruding from the first support surface and the second support surface
- 11 border opposed sides of the second elongated curved wiping edge of the
- 12 second squeegee element; and
- 13 [[c)] b) ~~means to couple the cleaning head to~~ a motorized handle that
- 14 automatically moves the first support surface relative to the second
- 15 support surface.

1 27. (Currently Amended) The cleaning ~~head device~~ of claim 26, wherein the ~~first support~~
2 ~~surface further comprises a second squeegee element protruding therefrom~~ the motorized
3 handle detachably couples to the cleaning head.

1 28. (Currently Amended) A device comprising a cleaning head, the cleaning head
2 comprising:

- 3 a) a first support surface with a first squeegee element with opposed walls that form
4 a first elongated and continuous wiping edge that encircles a portion of the first
5 support surface and is configured to treat a working surface, the first support
6 surface being configured to move;
7 b) a second support surface with a second squeegee element with opposed walls that
8 form a second elongated and continuous wiping edge that encircles a portion of
9 the first support surface and is configured to simultaneously treat the working
10 surface; and
11 c) bristles ~~protruding from positions between the first squeegee wiping element and~~
12 ~~the second squeegee wiping element and,~~

13 wherein at least one of the first support surface and the second support surface is
14 configured to automatically move independently and separately of the other of the first
15 support surface and the second support surface, while the cleaning head is coupled to a
16 motorized handle.

1 29. (Previously Presented) The device of claim 28, wherein a portion of the bristles protrude
2 from the first support surface.

1 30. (Previously Presented) The device of claim 29, wherein a portion of the bristles protrude
2 from the second support surface.

1 31. (Currently Amended) An electric toothbrush with a cleaning head, the cleaning head
2 comprising:

- 3 a) ~~bristles protruding from~~ a first support surface region with a first set of
4 bristle protruding therefrom; and
5 b) a second support surface region that is separate from the first region and
6 having with a second set of bristle protruding therefrom and a continuous

7 and substantially circular squeegee element that encircles a portion of the
8 second ~~region~~ support surface and the second set of bristles, wherein the
9 second ~~region~~ support surface is coupled to a drive mechanism for
10 automatically rotating or oscillating the second ~~region~~ support surface
11 independently and separately from the first support surface and wherein
12 the first set of bristles surround at least a portion of the continuous and
13 substantially circular squeegee element, and wherein the first ~~region~~
14 support surface is configured to rotate or oscillate.

1 32. (Currently Amended) The electric toothbrush of claim 31, further comprising bristles
2 ~~protruding from the portion of the second region that is encircled by the continuous a~~
~~squeegee element protruding from the first support surface.~~

1 33. (Currently Amended) An electric toothbrush with a cleaning head, the cleaning head
2 comprising:

- 3 a) a first region with a first support surface having a continuous and substantially
4 circular squeegee element that encircles bristles protruding from the first support
5 surface and wherein the first support surface is configured to rotate or oscillate;
6 and
7 b) a second region with a second support surface configured to automatically move
8 independently from the first ~~supports~~ support surface in at least one direction that
9 is different from the first support surface, the second support surface having at
least one of a squeegee, bristle tufts and nodules protruding therefrom.